



EMERGENCY PROCEDURE GUIDE – TRANSPORT

PROPSPEED – CLEAR COAT and PROP CLEAN

UN No.: 1263 and 1170
CLASS: 3 and 3
HAZCHEM: 3(Y) and 2(YE)

EMERGENCY CONTACTS

POLICE OR FIRE BRIGADE: DIAL 000

Organisation	Location	Telephone	Ask for
PR FLOORS	21 COMPUTER ROAD YATALA QLD 4207	07 – 3807 4422	BRAD AINSWORTH

MATERIAL SAFETY DATA SHEET

Statement of Hazardous Nature

Flammable liquid. Vapours are flammable and toxic.

Identification

Product Name: *PROPSPEED CLEAR COAT*
Other Names: Clear Non Toxic Coating
Manufacturers Code: PROPSPEED CLEAR COAT
UN Number: 1263
DG Class: 3
Hazchem Code: 3(Y)
Toxic Substances Schedule: Schedule 5 (exempt material..paints)
Uses: Clear non toxic foul release for marine use.

Physical Description/Properties

Appearance: Viscous Water White liquid
Boiling Point: 138 – 144°C
Vapour Pressure: 1333 pa
Percent Volatiles: 15% w /w
Specific Gravity: 1.00
Flash Point: 26°C
Flammability Limits: LEL 1.1 UEL 7.0% vol
Solubility in Water: Nil

Hazardous Ingredients

Chemical Entity	C.A.S. Number	Proportion
Xylol	1330-20-7	Low (<10%)

Health Hazard Information

Health Effects

Acute

Swallowed: Possible Nausea and vomiting. Likely to cause severe irritation and possible toxic reaction.

Eye: Contact will cause severe irritation.



EMERGENCY PROCEDURE GUIDE – TRANSPORT

PROPSPEED – CLEAR COAT and PROP CLEAN

UN No.: 1263 and 1170
CLASS: 3 and 3
HAZCHEM: 3(Y) and 2(YE)

Skin:	Prolonged or repeated contact may cause irritation and dermatitis.
Inhaled:	Vapours may irritate mucous membranes. Prolonged exposure may cause drowsiness and nausea and possible loss of consciousness in extreme cases.
Chronic Effects:	Prolonged or repeated exposure may cause asthma and skin sensitisation or other allergic response. Long term exposure to solvent vapours may cause changes to personality and loss of short term memory.

First Aid

Swallowed:	Do not induce vomiting. Give milk or water to dilute. Seek medical attention.
Eye:	Flush with copious quantities of clean water holding eyelids open. Seek medical attention immediately.
Skin:	Wash skin with soap and water. Remove contaminated clothing and shoes. Seek medical attention if reddening or swelling occurs.
Inhaled:	Move subject to fresh air. Administer artificial respiration or oxygen if necessary. Seek medical attention if effects persist.
Advice to Doctor:	None.
Spills and Disposal:	Prevent run-off into storm water drains or waterways with sand bags or absorbent material. Absorb onto sand and shovel into open top containers that can be sealed. Clean area with detergent and water. Dispose in accordance with local body requirements treating as liquid paint waste. Solventborne.

Fire & Explosion Hazard Data

Dot Category:	FLAMMABLE LIQUID
Extinguishing Medium:	CHEMICAL FOAM, DRY POWDER, CO2 OR WATER FOG
Flammability Limits:	LEL 1.1% UEL 7.0%

Special Fire & Explosion Hazards

Vapours are heavier than air and may travel along the ground and be ignited by ignition sources some distance away. Containers should be kept cool with water fog during a fire.

Special Fire Fighting Procedures

Water or foam may cause violent frothing which could endanger fire fighting staff by spraying flammable liquid. Self contained breathing apparatus should be used with full face protection.